



Available
in **black** or
white

VT-IP712-C3

Internal Forward-Facing IP Dome Camera

A high performance, forward-facing network dome camera in a rugged housing with super-wide dynamic range and sharp, crystal clear images.



Key Features:

- 1280 × 720p @ 30fps resolution
- Auto white light compensation
- IP66 waterproof
- Anti-vibration
- Vandal-proof
- Infra-red for night-time use

Specification*:

Camera Parameters	Sensor	1/3" CMOS Sony IMX238	
	Resolution	1280(H)x720(V)	
	Signal System	50/60Hz	
	Minimum Illumination	0.05 Lux (Color Illumination), F1.2	
	Electronic Shutter	1/25 Second -1/10000 Second	
	Wide Dynamic Range	Digital Wide Dynamic Range	
	Black-light Compensation	Support	
	S/N	>40db	
		Wide Dynamic Range	>80db
Optical Lens	Port	6-pin DJ M12(PON)/RJ45(POE)	
	Aperture	Fixed aperture F1.8	
	Lens	2.8mm, 4mm, 6mm, 8mm Optional	
Audio/Video Encode	Video Compression	H.264	
	Compression Output Rate	768Kbps-6144Kbps	
	Image Resolution	Main Stream: 720p @ 30fps, Network Sub Stream: VGA @ 25fps, Record Sub Stream	
		CBR/VBR	Support
		Built-in Mic	Support
		Audio Compression Standard	ADPCM G.711A G.711U
		Maximum Image	1280x720
Image	Frame	30FPS	
	Image Setting	Chroma, contrast, saturation and sharpness	
	Network Port	RJ45/M12-4 Aviation Din, 10M/100M Adjustable Ethernet Port	
Network	Network Protocol	HTTP,TCP,ARP,RTSP,UDP,RTCP,SMTP,DHCP,DNS, DDNS,PPPoE,IPV4,UPnP,NTP	
		ONVIF	Support
		Client Terminal Preview	Build-in WEB server; Support IE browser
		Audio Input (Optional)	Support
Ports	PoE	Support	
	Temperature	-40c-- + 70c	
Others	Humidity	0% - 90%	
	Power Supply	PON(DC12V)/POE(DC48V)	
	Waterproof Class	IP66 (IP65 with audio)	
	Power	<2w(Day)	
	Dimension (mm)	90(L)x110(W)x53(H)	

